

Technical drawing showing three types of door locks (A, B, and C) with their dimensions. The drawing includes front, top, and side views for each lock type.

Lock A Dimensions:

- Front View: Overall width 34, inner width 28.
- Top View: Overall width 34, inner width 28.
- Side View: Lock body height 40, handle height 3, handle offset 15, handle width 30, handle depth 8.5.

Lock B Dimensions:

- Front View: Overall width 34, inner width 28.
- Top View: Overall width 34, inner width 28.
- Side View: Lock body height 40, handle height 3, handle offset 15, handle width 30, handle depth 8.5.

Lock C Dimensions:

- Front View: Overall width 34, inner width 28.
- Top View: Overall width 34, inner width 28.
- Side View: Lock body height 40, handle height 3, handle offset 15, handle width 30, handle depth 8.5.

Common Dimensions:

- Lock body width: 25
- Lock body height: 34-43
- Lock body depth: 25-43
- Lock body offset: 20
- Lock body width: 34

Technical drawing of the 1000mm wide sliding door system, showing side and cross-sectional views with dimensions.

Side View Dimensions:

- Overall width: 143.5
- Overall height: 71
- Top rail height: 15
- Bottom rail height: 30 ±
- Intermediate height: 8.5

Cross-sectional View Dimensions:

- Top rail width: 25
- Top rail depth: 34-36
- Bottom rail width: 25
- Bottom rail depth: 34-36
- Door panel width: 20
- Door panel depth: 34
- Door panel height: 18.5
- Door panel thickness: 8 ±

Bezeichnung	Länge	Ausführung	Id.Nr.
Set Teleskop Perlan 2-flügelig zum teleskopischen Verfahren von Holzflügeln, bestehend aus: komplettem Teleskopmechanismus mit Montagematerial, Drahtseil 3,8 m, inklusive 4 x Aufhängeplatte Perlan 140 KS			130891
Set Teleskop Perlan Erweiterung 3-flügelig zur Erweiterung um 3. Flügel, inklusive 2 x Aufhängeplatte Perlan 140 KS			130892
Zubehör			
Set Montagewerkzeug zur Seilvernietung zur Vernietung des Drahtseils bei Perlan Teleskop			134035
Bodenführung M-Form	6000 mm	EV1	124661
Bodenführung durchgehend Omega-Form	6000 mm	EV1	124640
Bodenführung spielfrei Mit Befestigungsmaterial			123514
Puffer für durchgehende Bodenführung			124655
Puffer für durchgehende Glasbodenführung			124656
Riffelwinkel 100 mm für Bodenführung Mit Befestigungsmaterial			123513
Riffelwinkel 40 mm für Bodenführung Mit Befestigungsmaterial			123511
Riffelwinkel 60 mm für Bodenführung Mit Befestigungsmaterial			123512